

PARICÁ PLYWOOD FROM BRAZIL

TECHNICAL DETAILS

100% PARICÁ PLYWOOD						
THICKNESS	PLIES	SPECIES	RESIN/GLUE	FRONT-FACE	BACK-FACE	CORE
4mm	3	Parica 100%	WBP or MR	Parica 1.5mm	Parica 1.5mm	1 x Parica 1.5mm
5mm	3	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	1 x Parica 1.5mm
6mm	3	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	1 x Parica 2.1mm
9mm	5	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	2 x Parica 2.1mm + 1 x Parica 2mm
12mm	7	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	3 x Parica 1.5mm + 2 x Parica 2mm
15mm	9	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	4 x Parica 1.5mm + 3 x Parica 2mm
18mm	9	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	4 x Parica 2.1mm + 3 x Parica 2mm
22mm	11	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	5 x Parica 2.1mm + 4 x Parica 2mm
24mm	11	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	5 x Parica 2.5mm + 4 x Parica 2mm
28mm (*)	14	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	7 x Parica 2.1mm + 5 x Parica 2mm
30mm (*)	15	Parica 100%	WBP or MR	Parica 2mm	Parica 2mm	7 x Parica 2.1mm + 6 x Parica 2mm
Grades: BB/CC and CP/CP. Standard Sizes: 2500x1220 and 2200x1600mm. (*) 28 and 30mm only in size 2200x1220mm. Humidity: 8-12%.						
SPECIFICATIONS: WBP GLUE				SPECIFICATIONS: MR GLUE		
Weight: 470kg/m ³ . Pressure: 12-14 kgf/cm ² . Temperature: 115-125.				Weight: 450kg/m ³ . Pressure: 8-10 kgf/cm ² . Temperature: 95-115.		

PARICÁ PLYWOOD FROM BRAZIL

TECHNICAL DETAILS

PARICÁ COMBI PLYWOOD						
THICKNESS	PLIES	SPECIES	RESIN/GLUE	FRONT-FACE	BACK-FACE	CORE
4mm	3	COMBI	WBP or MR	Parica 1.5mm	Parica 1.5mm	1 x Eucalyptus 1.5mm
5mm	3	COMBI	WBP or MR	Parica 2mm	Parica 2mm	1 x Eucalyptus 1.5mm
6mm	3	COMBI	WBP or MR	Parica 2mm	Parica 2mm	1 x Eucalyptus 2.1mm
9mm	5	COMBI	WBP or MR	Parica 2mm	Parica 2mm	2 x Eucalyptus 2.1mm + 1 x Parica 2mm
12mm	7	COMBI	WBP or MR	Parica 2mm	Parica 2mm	3 x Eucalyptus 1.5mm + 2 x Parica 2mm
15mm	9	COMBI	WBP or MR	Parica 2mm	Parica 2mm	4 x Eucalyptus 1.5mm + 3 x Parica 2mm
18mm	9	COMBI	WBP or MR	Parica 2mm	Parica 2mm	4 x Eucalyptus 2.1mm + 3 x Parica 2mm
22mm	11	COMBI	WBP or MR	Parica 2mm	Parica 2mm	5 x Eucalyptus 2.1mm + 4 x Parica 2mm
24mm	11	COMBI	WBP or MR	Parica 2mm	Parica 2mm	5 x Eucalyptus 2.5mm + 4 x Parica 2mm
28mm (*)	14	COMBI	WBP or MR	Parica 2mm	Parica 2mm	7 x Eucalyptus 2.1mm + 5 x Parica 2mm
30mm (*)	15	COMBI	WBP or MR	Parica 2mm	Parica 2mm	7 x Eucalyptus 2.1mm + 6 x Parica 2mm
Grades: BB/CC and CP/CP. Standard Sizes: 2500x1220 and 2200x1600mm. (*) 28 and 30mm only in size 2200x1220mm. Humidity: 8-12%.						
SPECIFICATIONS: WBP GLUE				SPECIFICATIONS: MR GLUE		
Weight: 580kg/m ³ . Pressure: 12-14 kgf/cm ² . Temperature: 115-125.				Weight: 560kg/m ³ . Pressure: 8-10 kgf/cm ² . Temperature: 95-115.		

PARICA PLYWOOD FROM BRAZIL

PRODUCT PICTURES

FACE SIDE



CORE



PARICA PLYWOOD FROM BRAZIL

PRODUCT PICTURES

COUNTER-FACE SIDE

